


VHF MARINE TRANSCEIVER WITH DSC

World's Slimmest Floating DSC Radio



2.3" Large High Visibility LCD


2.3" large, high contrast and full dot-matrix LCD ensures good readability under direct sunlight. Large compass screens and large character size provide at-a-glance information.



Menu screen



Pop-up window for position check



Navigation screen



Slimmest* Floating DSC Radio

By adopting a flat sheet keypad, at 38.5 mm (1.52 in) the IC-M93D is the slimmest floating DSC handheld radio in the world. Fits comfortably in your palm for ease of use.

* As of June 2016, researched by Icom.



Intuitive User Interface

For an operator not familiar with DSC radio operation, the combination of the four directional keypad and soft keys provides straight-forward operation of all functions.



Built-in Class H DSC with a CH70 Receiver

A dedicated DSC receiver continuously monitors CH70. Distress calls can be made with the rear panel button.



Distress button



Float'n Flash and MOB Auto Set Function

The IC-M93D floats and flashes on the water. Pressing the distress button while Float'n Flash is working will transmit the MOB distress signal, rather than the plain undesignated one for better protection of sailors.



INTEGRATED
GNSS RECEIVER



ACTIVE
NOISE CANCEL



Integrated GNSS Receiver

The integrated GNSS receiver provides your location, bearing and speed with fast-setup time and pinpoint accuracy by using information from GPS, GLONASS, QZSS and SBAS.

Active Noise Canceling

Active Noise Canceling digitally removes background noise from both transmit and receive audio and provides clear communication in a noisy maritime environment.

Comes with Rapid Charger, BC-220

The supplied rapid charger, BC-220, charges the BP-285 in 3 hours (approx). The cigarette lighter cable, CP-25H, is also supplied.

Other Features

- IPX7 submersible (1 m depth of water for 30 minutes)
- Navigation function from current position to the specified waypoint
- 50 waypoint memories with alphanumeric name for navigation
- Weather channel receive with weather alert function
- Dual/Tri-watch function for monitoring CH16 and/or call channel
- Battery indicator shows remaining battery power in four levels
- Favorite channel function for quick access to often used channels
- AquaQuake™ draining function clears water away from the speaker grill
- When the HM-165 is connected to the IC-M93D, the HM-165 and the radio floats on the water

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

RECHARGEABLE Li-ion BATTERY PACK



BP-285
Li-ion 7.2 V,
1485 mAh (min.)
1570 mAh (typ.)

Provides 9 hours* of operating time.
* Typical operation with 5:5:90 (Power save: ON, while valid GNSS data is received.)


RAPID CHARGER



BC-123SA/SE* BC-220

Charges the BP-285 in 3 hours (approx.). * May differ depending on version. Photo shows BC-123SA.

MULTI-CHARGER



BC-214

Charges up to six BP-285 in 3 hours (approximately).

SPEAKER-MICROPHONES



HM-228
IPX7 compact type.

HM-165
IPX7 rugged type.

LEATHER BELT HANGERS



MB-96FL
Long fixed type.

MB-96F
Fixed type.

CIGARETTE LIGHTER CABLE



CP-25H
For use with BC-220.

ANTENNA FA-SC59V
Same as supplied.

BELT CLIP MB-133
Same as supplied.

CHARGER ADAPTER AD-133
Supplied with the BC-214, depending on version.

SPECIFICATIONS

GENERAL		
Frequency range	Tx Rx Rx (CH70)	156.025–157.425 MHz 156.050–163.275 MHz 156.525 MHz
Usable channel groups		INT, USA, CAN, WX channels
Type of emission		16K0G3E (FM), 16K0G2B (DSC)
Current drain (at 7.2 V DC)	Tx (5.0 W/1.0 W output) Rx (Inter SP/Exter SP Max. audio)	1.5 A/700 mA (approx.) 450 mA/250 mA (approx.)
Operating temperature range		–20°C to +60°C; –4°F to +140°F
Antenna impedance		50 Ω
Dimensions (W×H×D) (projections not included)		57.0×144.6×38.5 mm; 2.24×5.69×1.52 in
Weight (approximately)		300 g ; 10.58 oz (With BP-285, FA-SC59V, MB-133)

TRANSMITTER	
Output power (Hi/Low)	5 W/1 W
Max. frequency deviation	±5 kHz
Frequency stability	±10 ppm
Spurious emissions	–68 dBc typical

RECEIVER	
Sensitivity (at 12 dB SINAD)	0.25 μV typical
DSC receiver (at 1% BER)	–5 dBμ emf typical
Squelch sensitivity (Threshold)	0.25 μV typical
Adjacent channel selectivity	70 dB typical
DSC receiver (at 1% BER)	73 dBμ emf typical
Spurious response	70 dB typical
DSC receiver (at 1% BER)	73 dBμ emf typical
Intermodulation	70 dB typical
DSC receiver (at 1% BER)	68 dBμ emf typical
Hum and noise	40 dB
Audio output power (Internal SP)	900 mW typical (12 Ω load)
(at 10% distortion)	External SP 350 mW typical (8 Ω load)

Measurements made in accordance with TIA/EIA-603 and IEC 62238. All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

Supplied accessories:

- AC adapter, BC-123SA/SE*
- Belt clip, MB-133
- Battery charger, BC-220
- Antenna, FA-SC59V
- Battery pack, BP-285
- Hand strap
- Cigarette lighter cable, CP-25H * May differ depending on version.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com